

MINI PRESSURE SWITCHES



ELECTRICAL RATINGS

AC 120V/240V, DC 5V/12V Rated current 1A to 6A

DC 24 Rated current 1A to 4A

Application	Model	Code	Cut-out & tolerance bar	Cut-in & tolerance bar	Reset	Contact system type	Connections Solder		Connections Flare	Cable length (mm)
							6 mm	¼ inch	Female (with depressor)	
Hight pressure Cut-out	MPS2AH17	10570001901	19 ±1	15 ±1.5	Auto	SPST-NC	•			1000
	MPS2AH26	10570004101	26 ±1	20 ±1.5	Auto	SPST-NC		•		2000
	MPS2AH29	10570002401	31 ±1	24 ±1.5	Auto	SPST-NC	•			1500
	MPS2AH82 ¹⁾	10570004801	30 ±1	25 ±1.5	Auto	SPST-NC		•		
	MPS2AH01	10570000301	41.5 +0/-1.5	32 ±2	Auto	SPST-NC		•		1000
	MPS2AH02	10570000101	45 +0/-3	34 ±2	Auto	SPST-NC		•		1000
Low pressure Cut-out	MPS1AH13	10570004201	0.3 ±0.3	1.2 ±0.3	Auto	SPST-NO	•			2000
	MPS1AH09	10570003401	0.6 ±0.5	1.8 ±0.4	Auto	SPST-NO	•			1000
	MPS1AH12	10570002501	0.7 ±0.5	1.7 ±0.4	Auto	SPST-NO	•			1500
	MPS1AL01	10570000901	1 ±0.2	1.6 ±0.2	Auto	SPST-NO			•	1000
Fan control	MPS2AL05 ²⁾	10570001101	9 ±0.5	12 ±0.7	Auto	SPST-NO			•	1000

Note: 1) model with tab terminals
 2) with AMP 2-520263-2 connectors on electrical cables