



ZJF SERIES

RECEIVER VALVE

(Standard range: for fluids GROUP 2 according to Directive 2014/68/EU or GROUP A1 according to ANSI-ASHRAE 34-2016).

Receiver valves are used for tube connection of compressors and reservoirs of commercial air conditioner, freezing or deep-freezing equipment. Inner path of the valve can be closed or opened by operating the valve stem.




FEATURES

- COST EFFECTIVE: OPTIMAL DESIGN BASED ON PERFORMANCE
- GOOD APPEARANCE AND ENDURABLE: THE VALVE BODY TREATED WITH SHOT BLAST.
- WELL SEALING PERFORMANCE: WITH PARTICULAR SEALING STRUCTURE AND DESIGN

GENERAL SPECIFICATIONS

- Applicable refrigerant: R22, R134a, R407C
- Applicable medium temperature: $-40^{\circ}\text{C} \div +120^{\circ}\text{C}$
- Maximum working pressure: 4.2 MPa
- Certification: UL, Declaration according PED



| Model | A | F | Dimensions [mm] | | | |
|---------------|--------------|---------|-----------------|------|------|----|
| | | | B | C | D | E |
| ZJF-A22SHC-35 | 7/16-20UNF | NPT 1/4 | 4.8 | 23.5 | 74.3 | 24 |
| ZJF-A33SHC-51 | 5/8-18UNF | NPT 3/8 | 7 | 27 | 77 | 27 |
| ZJF-A44SHC-48 | 3/4-16UNF | NPT 1/2 | 10 | 36 | 119 | 37 |
| ZJF-A54SHC-57 | 7/8-14UNF | NPT 1/2 | 12.5 | 36 | 119 | 37 |
| ZJF-A66SHC-65 | 1 1/16-14UNS | NPT 3/4 | 16 | 48 | 122 | 43 |
| ZJF-A76SHC-58 | 1 1/4-12UNF | NPT 3/4 | 20 | 48 | 122 | 43 |

For complete product family information please visit us at www.sanhuaeurope.com and download the full range of datasheet at TECHNICAL INFORMATION LINK.